

MATERIAL DESCRIPTION

Coala Floor & Wall R is a 150 micron textured white PVC laminated with a removable clear acrylic adhesive. The product is for short to medium term indoor applications. The product is suitable for printing by Latex, UV & most solvent based inks.

PRINTER & INK COMPATIBILITY



FACE MATERIAL

150
µm

FEATURES

- Face material: Textured White Monomeric PVC > 150 µm ± 10
- Adhesive: Acrylic water based PSA moderate tack > 26 µm ± 2
- Liner: Structured air release, 1 side siliconized > 135 µm ± 10
- Standard Sizes: 1370 mm (W) x 50 m (L)
- Slip test: R10
- Fire Test: C-s1 d0

BENEFITS

- Clean remove product, however minimal residue can transfer on to surface
- For ease of application Coala Floor & Wall R is supplied with an 'air free' structured release liner
- Slip Resistant
- Fire Resistant
- No lamination required
- Good scratch resistance

APPLICATIONS

- Short to Mid Term Application
- Indoor Use
- POS Signage/ General Signage
- Wall Graphics
- Floor Graphics - Applicable to
 - floor tiles,
 - pvc flooring,
 - concrete/stone floor
 - wooden/laminated floors
 - carpets (low pile carpets - but should be tested on small area to prove performance)



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

