



## COALA IN & OUT TEXTILE

### Product Information

185 g polyester waterproof / flame retardant and impermeable to air for Aluminium Frames / Inflatables / Outdoor banners

Unique product

Completely waterproof

Flame retardant

Impermeable to air.

Crack resistant to +5 ° C

Prints great with Solvent, UV and Latex Ink

B1 fire resistant

Oeko tex, PVC Free

### Technical data

Product:	Coala In & Out Textile	Unit	Standard
Substrate	100 % Polyester		DIN 6001
Ends / Picks	23 / 17	Fd / cm	DIN 1049-2
Yarn	334 / 334	dtex /Nm	DIN ISO 2060
Weave	Plain weave		DIN ISO 9354
Grammage	185 ± 15	g/m2	DIN ISO 2286-2
Thickness	0,25 ± 0,02	mm	DIN ISO 2286-3
Tensile strength warp/weft	> 55 / 65	daM/5cm	DIN ISO 13934-1
Tear resistance warp/weft	> 20 / 15	[N]	DIN ISO 13937-1
Whiteness	≥ 100		Berger
Light fastness	≥ 7	Grade	DIN ISO 105-B02
Water pressure test	> 950	mm	DIN 20811 ISO 811 or DIN 53886
Air Permeability	< 0,50	l / dm <sup>2</sup>	DIN 4102 B1 or DIN 53887
Flame Retardant	B1		DIN 4102 B1 NFPA 701, CA 1237

### Standard Dimensions

1000 mm x 50 m  
1370 mm x 50 m  
1520 mm x 50 m  
1620 mm x 50 m  
2500 mm x 50 m  
3080mm x 50 m



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.





C  ALA

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

