

MATERIAL DESCRIPTION

Coala Roll-up PET W is a 180 mic polyester with silver back, high opacity and stiffness with very good flatness. After the completed drying process the print-outs are very durable and can also be used without the application of an additional protective lamination. White, low reflective inkjet coating layer. Can be printed with dye and pigmented ink systems.

PRINTER & INK COMPATIBILITY



FILM THICKNESS

180
μ

GRAMMAGE

215
g/m²

PRODUCT DESCRIPTION

- Carrier: Coated PET film
- Thickness: 180 ± 30 mic (DIN EN 20534*)
- Grammage: 215 ± 30 g/m² (ISO 536)
- Gloss (60°GE | 60°GU) : 3,0
- Opacity: 100 %

RECOMMENDATIONS

- Prints have to be completely dry before undergoing further processing or lamination.
- To avoid damage to the laminated material, it is essential to use sharp blades at an acute angle. However delamination cannot be entirely excluded.
- Limited dimensional stability when heated. If drying temperature is too high, then the material buckles.

SHELF LIFE STORAGE AND CONDITIONS



- In original packaging in a cool and dry environment at a temperature of 10°C to 25°C and at a relative humidity of 35% to 65%.
- Processing: within two year after receipt

APPLICATIONS

- Roll-up
- Posters
- Points of sales
- Trade show graphics
- POS advertisement for indoor and outdoor areas

BENEFITS

- High opacity and stiffness
- Very good flatness
- High optical density due to the blackout effect
- Brilliant color density and greated resistance to color degradation with pigmented inks
- Fast drying
- High tearing strength

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

