

For guidance only



PRODUCT SPECIFICATION

IDEM SUPERIOR SHEETS

GRADE	CB 100
--------------	---------------

COPY COLOUR	BLACK
--------------------	--------------

PROPERTY	METHOD	UNITS	RANGE		
			MIN	TARGET	MAX
GRAMMAGE	ISO 536 - 1995	gm ⁻²	95.0	-	105.0
THICKNESS	ISO 534 - 1988	µm	121	127	133
ROUGHNESS - BASE SIDE	ISO 8791 (Part 2) - 1990	ml min ⁻¹	100	150	350
ROUGHNESS - CB SIDE	ISO 8791 (Part 2) - 1990	ml min ⁻¹	200	400	600
STIFFNESS - MD	ISO 2493 - 1992	mN	160	210	260
STIFFNESS - XD	ISO 2493 - 1992	mN	60	90	120
TENSILE STRENGTH - MD	ISO 1924 (Part 1) - 1992	N/15 mm	85	-	-
TENSILE STRENGTH - XD	ISO 1924 (Part 1) - 1992	N/15 mm	40	-	-
RELATIVE HUMIDITY	CPOTM 2:27	%	30	37.5	45
DIMENSIONAL STAB. - MD	ISO 8226 (Part 1) - 1985	%	-	-	0.2
DIMENSIONAL STAB. - XD	ISO 8226 (Part 1) - 1985	%	-	-	0.6
50 % RH CURL - CB/BASE	CPOTM 2:12	mm	5	0	5
IMAGE INTENSITY	CPOTM 2:54	% Refl.	33	38	44
OPACITY	CPOTM 2:21	% Refl.	89	92	-
BRIGHTNESS	ISO 2470	% Refl	99	103	107

ISSUE NR 6	PAGE 1 OF 1	DATE : 03/03/2010
Authorisation	Director Customer Technical Services	P. Marneffe